

Polycom Conference Phone Guide

IP conference phones	Large room		Standard conference room			Small room and office
	Polycom® RealPresence Trio™	Polycom® SoundStation® IP 7000	Polycom [®] SoundStation [®] Duo	Polycom® CX3000	Polycom [®] SoundStation [®] IP 6000	Polycom [®] SoundStation [®] IP 5000
Call platform connectivity						
IP (SIP)	•	•	•		•	•
Skype for Business/Office 365/Lync	•		Lync only	Optimized		Lync only
Analog			•			
Voice quality						
Polycom [®] HD Voice [™] technology	•	•	•	•	•	•
Loudspeaker frequency response	100 Hz - 22 kHz	160 Hz—22 kHz	220 Hz—7 kHz	200 Hz—7 kHz	220 Hz—14 kHz	250 Hz—7 kHz
Microphone pickup range	6 m/20 ft	6 m/20 ft	3 m/10 ft	3.6 m/12 ft	3.6 m/12 ft	2 m/7 ft
Intelligent microphone mixing	•	•	•	•	•	•
Dynamic noise reduction	•	•	•	•	•	
NoiseBlock™	•					
Automatic gain control	•	•		•	•	
Additional features						
Resists interference from wireless devices	•	•	•	•	•	
Software upgradable	•	•	•	•	•	
Large display to support advanced applications		•		•		
Large color touch screen user interface	•					
Multi-unit connectivity		•				
Connect to external audio system	•	•(1)				
Computer/mobile device connectivity	•	•				
Wi-Fi network connectivity ⁽²⁾	•					
Bluetooth enabled	•					
Optional accessories						
Expansion microphones (wired)	•	•	•	•	•	
Wireless lapel pin microphone		• (NA only)			• (NA only)	
Video integration kit or cables		•				
Computer calling kit			•			
Mobile device cables		•	•			
RealPresence Trio Visual + (enables content and video capability)	•					
Power Kit	•					
Model variants						
Power over Ethernet (PoE)	2200-66070-001	2200-40000-001		2200-15810-025	2200-15600-xxx	2200-30900-025
AC or Power over Ethernet (PoE)		2230-40300-001	2200-19000-xxx		2200-15660-xxx	2200-30900-xxx
Lync/Skype for Business Edition (PoE)	2200-66070-019					
AC Power only	2200-13339-001	•	•	•		

¹ Optional accessory required

² Available when used as a conference phone only (not for use with RealPresence Trio Visual+)

Analog conference phones	Large room	Sta	Small room and office		
	Polycom [®] SoundStation VTX 1000 [®]	Polycom [®] SoundStation2™	Polycom® SoundStation® Duo	Polycom [®] SoundStation2W™	Polycom® VoiceStation® 300
			5 10 10 10 10 10 10 10 10 10 10 10 10 10		
Network connectivity					
Analog	•	•	•	•	•
IP (SIP)			•		
Microsoft Lync			•		
Voice Quality					
Polycom HD Voice technology			•		
Loudspeaker frequency response	80 Hz—7 kHz ⁽⁵⁾	300 Hz—3300 Hz	220 Hz—7 kHz	300 Hz—3500 Hz	300 Hz – 3300 Hz
Microphone pickup range	6 m/20 ft	3 m/10 ft	3 m/10 ft	3 m/10 ft	2 m/7 ft
Intelligent microphone mixing	•	•	•	•	•
Dynamic noise reduction	•	•	•	•	•
Automatic gain control	•				
Additional Features					
Resists interference from wireless devices	•	•	•	•	•
Software upgradable	•		•	•	
Large display to support advanced applications					
Multi-unit connectivity					
Connect to external audio system	•	•		•	
Bluetooth connectivity					
Optional accessories					
Expansion microphones (wired)	•	•(3)	•	•(4)	
Wireless lapel pin microphone	•	•			
Video integration kit or cables	•				
Computer calling kit		•(3)	•	•(4)	
Mobile device cables		•(3)	•	•(4)	
Model variants					
	2200-07142-xxx (with EX mics only)	2200-15100-xxx (non expandable w/o display)	2200-19000-xxx	2200-07800-xxx (expandable)	2200-17910-xxx
	2200-07300-xxx (w/o EX mics and subwoofer)	2200-16000-xxx (non- expandable, w/display)			
	2200-07500-xxx (with subwoofers only)	2200-16200-xxx (expandable, w/display)			

³ Available on selected models

About Polycom

Polycom helps organizations unleash the power of human collaboration. More than 400,000 companies and institutions worldwide defy distance with video, voice and content solutions from Polycom. Polycom and its global partner ecosystem provide flexible collaboration solutions for any environment that deliver the best user experience and unmatched investment protection.

Polycom, Inc. 1.800.POLYCOM www.polycom.com Polycom Asia Pacific Pte Ltd +65 6389 9200

www.polycom.com.sg

Polycom EMEA +44 (0)1753 723282 www.polycom.co.uk



⁴ SoundStation VTX to SoundStation VTX