



## LMP DATAMOBILE ULTRA SSD

M.2 PCIe NVMe SSD enclosure





M.2 PCIe NVMe SSD LMP DataMobile Ultra SSD

### PRODUCT OVERVIEW

Storage with highest performance, with a pocket-size design and (near) universal connectivity with bus-powered operation – the LMP DataMobile Ultra SSD incorporates these stunning features in an elegant all aluminum housing at a low cost.

The DataMobile Ultra SSD can be fitted with the latest ultra-fast M.2 PCle NVMe SSDs in sizes of 22×40 mm, 22×60 mm or 22×80 mm. Thanks to the screwless design, the installation is done within seconds. A set of cooling pads can be directly mounted onto the SSD, generating a thermal bridge so the evolving heat is dissipated away from the inside and its electronic parts. The rugged aluminum enclosure then acts as a perfect heat sink while protecting the data during the transport. The high-performance Type C (USB-C) Gen 2 (10G) bridge transfers data with up to 900 MB/s in real life scenarios.

Ever experienced the moment when you storage cable does not fit with the host you want to exchange data with? To prevent this from happening, we supply a 2-in-1 USB-C to USB-A & USB-C cable. One cable, two connections – whether legacy USB 3.0/2.0 or state-of-the-art USB-C, the DataMobile Ultra SSD can be connected.

Carry your data in your pocket, transfer data with high-speed and no headache about the port the host will have – that's the LMP DataMobile Ultra SSD.

#### P/N 20357

#### **KEY FEATURES**

- Type C 3.1 Gen 2 (10G) PCBa with real data transfer rates up to 900 MB/s
- Supports PCIe NVMe protocol storage
- Fits 3 sizes of M.2 PCle NVMe SSDs: 22x40 mm, 22x60 mm and 22x80 mm
- Rugged aluminum enclosure with ideal heat dissipation (cooling pads included) and screwless design
- Ultra-slim size (11x3x1.4 cm) and minimal weight (37 gr)
- 2-in-1 USB-C to USB-A & USB-C data cable included



#### M.2 PCIe NVMe SSD LMP DataMobile Ultra SSD

# TECHNICAL SPECIFICATIONS

#### **CONNECTIONS**

1x USB-C (USB 3.1 Type C Gen 2/10G) compatible with USB 3.0, USB 2.0 USB-C & USB-A (2-in-1), wired

#### TRANSFER RATE

Max. 10 Gbps (USB 3.1, Gen 2/10G)

#### **POWER DELIVERY**

USB bus-powered

#### MATERIAL

Aluminum

#### COLOR

Black and gray

#### **DIMENSIONS**

 $110 \times 30 \times 14 \text{ mm (l x h x w)}$ 

#### **WEIGHT**

37 gr

#### SYSTEM REQUIREMENTS

Mac OS X, macOS 10.12 and higher, Windows 7 and higher

#### **PACKAGE CONTENT**

Enclosure, 2-in 1 USB-C to USB-C & USB-A cable (15 cm), cooling pads for SSD

#### **EAN CODE**

7640113434632

#### **COMPATIBILITY**

M.2 PCIe NVMe SSD 2242 (22x42 mm), 2260 (22x60 mm), 2280 (22x80 mm)



M.2 PCIe NVMe SSD LMP DataMobile Ultra SSD

## **PICTURES**





